




Move your products to the shelf edge!



The Optimal™+ shelf system includes a wide variety of merchandising solutions and is the culmination of many years' extensive research & development. Optimal™+ solutions include dividers, front feeding solutions and other accessories to keep your shelves neat and tidy.





This ensures product visibility and provides immediate visual identification of out-of-stocks.

The adjustable back support allows packs to be presented face-up without sliding forward. The solution also improves stock control.



⊃ DIVIDERS OPTIMAL+™



OPT-AVD25+

25 divider


25 mm high Optimal+ divider. Available in lengths 185 to 585 mm in steps of 25 mm. Number per unit: 24.





60 divider

60 mm high Optimal+ divider with a contemporary curved design. Available in lengths 235 to 585 mm in steps of 25 mm. Number per unit: 24.





120 divider

120 mm high Optimal+ divider with a contemporary curved design. Available in lengths 285 to 585 mm in steps of 25 mm. Number per unit: 24.





200 divider

200 mm high Optimal+ divider with a contemporary curved design. Available in lengths 385 to 635 mm in steps of 50 mm. Number per unit: 5.

⇒ BREAKABLE DIVIDERS OPTIMAL+™







Breakable 25 divider

Breakable Optimal+ divider in height 25 mm.
Three base lengths are available: 185-335, 335-485 and 485-635 mm.
Each base length has break points every 25 mm.
Number per unit: 24.



OPT-AVD60B+



Breakable 60 divider

Breakable Optimal+ divider in height 60 mm. Three lengths available: 185-385, 285-485 and 385-585 mm. Break points every 25 mm. Number per unit: 24.




OPT-AVD120B+



Breakable 120 divider

Breakable Optimal+ divider in height 120 mm. Three lengths available: 185-385, 285-485 and 385-585 mm.
Break points every 25 mm.
Number per unit: 24.

⇒ FRONT STOP DIVIDERS OPTIMAL+™







60 T-divider with low front

Optimal+ T-divider in height 60 mm with a front stop of 30 mm. Available in lengths 235 to 585 mm in steps of 25 mm.

Number per unit: 16.





OPT-AVD60L3+



60 L-divider with low front

Optimal+ L-divider in height 60 mm with a front stop of 30 mm. Available in lengths 235 to 585 mm in steps of 25 mm.

Number per unit: 20 (10 left and 10 right).



OPT-AVD60T+



60 T-divider

Optimal+ T-divider in height 60 mm. with a front stop of 60 mm. Available in lengths 185 to 585 mm in steps of 25 mm. Number per unit: 16.



OPT-AVD60L+



60 L-divider

Optimal+ L-divider in height 60 mm with a front stop of 60 mm. Available in lengths 185 to 585 mm in steps of 25 mm. Number per unit: 20.



OPT-AVD120T3+



120 T-divider with low front

Optimal+ T-divider in height 120 mm with a front stop of 30 mm. Available in lengths 285 to 585 mm in steps of 25 mm. Number per unit: 16.



OPT-AVD120T+



120 T-divider

Optimal+ T-divider in height 120 mm with a front stop of 80 mm. Available in lengths 285 to 585 mm in steps of 25 mm. Number per unit: 16.







120 T-divider with high front


Optimal+ T-divider in height 120 mm with a front stop of 120 mm. Available in lengths 185 to 585 mm in steps of 25 mm. Number per unit: 16.





 $\begin{array}{l} \textbf{120 divider for big T-front} \\ \text{Optimal+ 120 mm high divider with connection for big T- and L- fronts.} \\ \text{Available in lengths 185 to 585 mm in steps of 25 mm.} \end{array}$ Number per unit: 20.






Big T-front

To be used with OPT-AVD120CT+
Height = 128 mm.
Width = 100 mm.
Number per unit: 20.





Big L-front

To be used with OPT-AVD120CT+ Height: 128 mm.

Width: 50 mm. Number per unit: 20 (10 left and 10 right).






120 gravity feed divider for clip-on fronts
Can be used together with front riser OFRK80-AF30- or with clip on fronts OCT-100GR and OCT-CMGR.

Available in lengths 285 to 585 in steps of 25 mm. Number per unit: 20.





OCT-100GR



Big T-front for gravity

To be used with OPT-AVD120-AF30CT+. Height: 120 mm. Width: 100 mm. Number per unit: 20.



OCL-100GR



Big L-front for gravity

To be used with OPT-AVD120-AF30CT+. Height: 120 mm. Width: 50 mm. Number per unit: 20 (10 left and 10 right).





OCT-CMGR



T-Front with larger base

To be used with OPT-AVD120-AF30CT+. Height: 120 mm.
Width: 100 mm at the bottom, 30 mm at the top. Number per unit: 10.





OCL-CMGR



L-Front with larger base

To be used with OPT-AVD120-AF30CT+. Height: 120 mm. Width: 58 mm at the bottom, 16 mm at the top. Number per unit: 10 (5 left and 5 right).





OPT-AVD200T+



200 T-divider

Optimal+ T-divider in height 200 mm with a front stop of 180 mm. Available in lengths 385 to 635 mm in steps of 50 mm. Number per unit: 5.

 \oplus

○ FRONT STOP DIVIDERS - BREAKABLE OPTIMAL+™




OPT-AVD60BT3+



Breakable 60 T- divider with low front

Breakable Optimal+ T-divider in height 60 mm with a 30 mm high front stop. Three lengths available: 185-385, 285-485 and 385-585 mm.

Break points every 25 mm. Number per unit: 16.



OPT-AVD60BL3+



Breakable 60 L- divider with low front

Optimal+ L-divider in height 60 mm with a 30 mm high front stop. Three lengths available: 185-385, 285-485 and 385-585 mm.

Break points every 25 mm.

Number per unit: 20 (10 left and 10 right).



OPT-AVD60BT+



Breakable 60 T-divider

Breakable Optimal+ T-divider in height 60 mm with a 60 mm high front stop. Three base lengths available: 185-385, 285-485 and 385-585 mm.

Each base length has breaking points every 25 mm. Number per unit: 16.




OPT-AVD60BL+



Breakable 60 L-divider

Breakable Optimal+ L-divider in height 60 mm with a 60 mm high front stop. 3 base lengths are available: 185-385, 285-485 and 385-585 mm.

Each base length has break points every 25 mm. Number per unit: 20 (10 left and 10 right).



OPT-AVD120BT3+



Breakable 120 T-divider with low front

Breakable Optimal+ T-divider in height 120 mm with a front stop of 30 mm. Available in lengths 285 to 585 mm in steps of 25 mm. Number per unit: 16.





OPT-AVD120BL3+



Breakable 120 L-divider with low front

Breakable Optimal+ L-divider in height 120 mm with a front stop of 30 mm. Available in lengths 285 to 585 mm in steps of 25 mm. Number per unit: 20 (10 left and 10 right).



OPT-AVD120BT+



Breakable 120 T-divider

Breakable Optimal+ T-divider in height 120 mm with a 80 mm high front stop.

Three lengths are available: 185-385, 285-485 and 0385-0585 mm.

Each base length has break points every 25 mm.

Number per unit: 16.



OPT-AVD120BL+



Breakable 120 L-divider

Breakable Optimal+ L-divider in height 120 mm with a 80 mm high front stop..

Three lengths are available: 185-385, 285-485 and 385-585 mm.

Each base length has break points every 25 mm. Number per unit: 20 (10 left and 10 right).



OPT-AVD120BT12+



Breakable 120 T-divider with a high front

Breakable Optimal+ T-divider in height 120 mm with a 120 mm high front stop.

3 base lengths are available: 185-385, 285-485 and 385-585 mm.

Each base length has break points every 25 mm.

Number per unit: 16.



OPT-AVD120BL12+-



Breakable 120 L-divider with a high front

Breakable Optimal+ L-divider in height 120 mm with a 120 mm high front stop.

3 base lengths are available: 185-385, 285-485 and 385-585 mm.

Each base length has break points every 25 mm. Number per unit: 20 (10 left and 10 right).



□ BACK SUPPORT SYSTEMS OPTIMAL+™







Track for Back Support

Track used with adjustable back support (OPRS) for OptimalTM. One, breakable length, 0285-0485. Number per unit: 20.



OPRS



Back Support

Back support used with tracks ES-OPSS or OPSS. Number per unit: 20





Large track that works together with the OPRL back support and the OPRL-PIN-. Available in lengths: 384, 439, 483, 538 and 582 mm. Colour: Transparent. Number per carton: 20.



OPRL



Large back support

To be used together with the OPSL and the OPRL-PIN-. Height: 110 mm. Width: 95 mm. Colour: Transparent. Number per carton: 20.



OTPL-0117-0200



Large back plate

Support for larger products.
The OPTL-0117-0200 is used together with the OPRL.

Height: 200 mm. Width: 117 mm. Colour: Transparent. Number per unit: 20.







Large tool for manual feeding

Pull-Strip™ used with OPSL and OPRL. The Pull-Strip™ allows manual feed of the products from the front of the shelf. Available in lengths: 384, 444, 488, 543 and 587 mm.

Colour: Transparent.

Number per carton: 20.

⊃ PULL-STRIP™ OPTIMAL+™





Large Pull-Strip™

50 mm wide manual unit with integral Pull-Strip[™]. Height: 73 mm. Available in lengths 185 to 585 mm in steps of 25 mm. Number per carton: 20.



Large pusher

50 mm wide pusher for Optimal+. Available with standard spring strengths 3, 6 or 9. Height of pusher back plate: 73 mm. Available in lengths 185 to 585 mm in steps of 25 mm. Number per carton: 20.



OP50B+



Large breakable pusher

Breakable pusher for Optimal+ in width 50 mm with standard spring strengths 3, 6 or 9.

Height of pusher back plate: 73 mm.

For end stop use OP50B-STOP or OP50B STOP-MINI 3 base lengths are available: 185-385, 285-485 and 385-585 mm.

Each base length has break points every 25 mm.

Number per carton: 20.



OP50B-STOP-MINI+




Back stop for large breakable pusher

Pusher stop that can be fitted at each break point of a breakable OP50 pusher. Stops the pusher back plate from gliding off the back end of the pusher track, once mounted. Fits all brekable OP50 pusher tracks.

Number per unit: 20.



OSP-60-90



Large back plate

Back plate for larger packs sizes. To be used with OP50-PIN or OP50 pusher.

Colour: White. Height: 90 mm. Width: 60 mm. Number per unit: 20.



OSPA-80-130



Back Plate for larger packs.

To be used with OP50 pusher. Can be fixed into two angles 20 and 90

20 degree angle can either be used on flat shelving for backward leaning pack presentation, or as a gravity pusher on angled shelving.

Colour: Grey. Height: 130mm. Width: 80mm. Number per unit: 10



HDF



Clip-on back support for HL pushers

To re-size pusher backs or to create a message holder.

Easily assembled with a stable final result.

Standard sizes 100x100 or 150x150 mm. Other sizes on request.

Graphics: Screen-printed.

Material: Clear non-reflective 1,0 mm or white.

Number per box: 100x100 mm: 200 pcs, 150x150 mm:

100 pcs.





OP50-FL



Front package riser

To be mounted on to the OP50 pusher. With this product the first package available in the lane will be raised for ease of removal. Height: 8 mm.
Width: 50 mm.
Number per unit: 20.



OP50-FLF



Straight front stop

Clipped onto a OP50 track. Height: 50mm. Width: 58mm Colour: Transparent. Number per bag:10



OP50-FLF20



Angled front stop

Leans back 20 degrees and clipped onto a OP50 track. Height: 65mm. Width: 65mm Colour: Transparent. Number per bag: 10





OPGP-



Glide plate

Gravity slide to be used on the shelves. Dividers will fit on top of the glide plate. Available in different sizes. Colour: White. Number per unit: Bulk.









Narrow glider for angled shelves and pushers

Gravity slide to be used on the shelves. To be mounted together with T-dividers. Length: 185-635 mm. Width: 42 mm. Number per unit: 20.



OGFHL-



Narrow glider for angled shelves and pushers

Gravity slide to be used on the right and left ends of the shelf

To be mounted together with L-dividers.

Length: 185-635 mm. Width: 21 mm. Number per unit: 20.



OGFFT-



Glider for angled shelves

Gravity slide to be used on the shelves. To be mounted together with T-dividers. Length: 185-635 mm.
Width: 54 mm.

Number per unit: 20.



OGFFL-



Glider for angled shelves

Gravity slide to be used on the right and left ends of the shelf.

To be mounted together with L-dividers.

Length: 185-635 mm. Width: 27 mm. Number per unit: 20.



OPGT96-



Wide glider for both angled shelves and pushers

Gravity slide to be used on the shelves. To be mounted together with T-dividers. Length: 185-635 mm.
Width: 96 mm.





OPGL96-



Wide glider for both angled shelves and pushers

Gravity slide to be used on the right and left ends of the shelf.

To be mounted together with L-dividers.

Length: 185-635 mm. Width: 48 mm.

Number per unit: 20.

○ TOBACCO OPTIMAL™



OP-SPC-x-KIT



Push feeding solutions without pusher track

Pusher with front clip, with standard spring and integrated product riser. Pusher force: 2, 3 or 6. Number per unit: 50



OP-SPF-x-KIT



Push feeding solutions without pusher track

With front riser in width 45 mm. Standard spring. Integrated product riser. Pusher force: 2, 3 or 6. Front height: 40 mm. Number per unit: 50



OP-SPCS-x-KIT



Push feeding solutions without pusher track

Spring pusher with front clip, with integrated product riser. Pusher force: 3. Number per unit: 50





OP-SPFS-x-KIT



Push feeding solutions without pusher track

Spring pusher with front riser in width $45\mathrm{mm},$ with integrated product riser. Pusher force: 3. Front height: 40 mm Number per unit: 50



OP50WS-x-



Large pusher

50 mm wide pusher without the stop at the back. Available with standard spring strengths 3, 6 or 9. Height: 73 mm. Available in lengths 185 to 585 mm in steps of 25 mm.

Number per carton: 20.



OP50B-x-




Large breakable pusher

Breakable pusher in width 50 mm with standard spring strengths 3, 6 or 9. Height: 73 mm. 3 base lengths are available: 185-385, 285-485 and 385-585 mm. Each base length has break points every 25 mm.

Number per carton: 20.



OP50B-FLA



Large Breakable pusher.

Integrated product riser with spring strengths 3, 6, 9. Height: 73 mm. 3 base lengths are available: 185-385, 285-485 and 385-585 mm.

Each base length has break points every 25 mm. Number per carton: 20.





Narrow pusher

25 mm wide pusher with standard spring strengths 3, 6 or 9. Height: 55 mm.

Available in lengths 185 to 585 mm in steps of 25 mm. Number per carton: 20.





OP25B-x-



Narrow breakable pusher

Breakable pusher in width 25 mm with standard spring strengths 3, 6 or 9.

Height: 55 mm.

3 base lengths are available: 185-385, 285-485 and


385-585 mm.

Each base has break points every 25mm.

Number per carton: 20.



OMPH



Message plate

Message holder to be used on the sledge of OP50-PIN or OP50 pusher. Colour: Transparent.

Height: 58 mm. Width: 42 mm. Number per unit: 20.



OPT-AVD35RBTA-



Breakable 35 T-divider

Breakable T-divider in height 35 mm with a 30 mm high T front. One length available: 185-410 mm. Break points every 25 mm. Number per unit: 20.



OPT-AVD35RBLA-



Breakable 35 L-divider

Breakable L-divider in height 35 mm with a 30 mm high L front. One length available: 185-410 mm. Break points every 25 mm. Number per unit: 20.



OPT-AVD35RB-



Breakable 35 divider

Breakable divider in height 35 mm. To be used with a front riser. One length available: 185-410 mm. Break points every 25 mm. Number per unit: 20.





OPT-BOX30-xxx



Injection moulded pusher tray for "slimpack" cigarettes

Pusher with standard spring strengths 2 or 3. Lengths: 185, 270, 285, 260, 310, 335, 339, 360 and 435 mm. Transparent. Number per unit: 20.



OPT-BOX45-xxx

Injection moulded pusher tray for 10 pack cigarettes

Pusher with standard spring strengths 2 or 3. Available in lengths: 185, 210, 235, 260, 285, 310, 360, 385 and 410 mm. Colour: Transparent. Number per unit: 20.



Injection moulded pusher tray for 20 pack cigarettes

Pusher with standard spring strengths 2 or 3. Lengths: 170, 285, 335 and 360 $\,$ mm. Transparent. Number per unit: 20.





OPT-BOX59-xxx

Injection moulded pusher tray for 20 pack cigarettes

Pusher with standard spring strengths 2 or 3.

Available in lengths: 185, 210, 235, 260, 285, 310, 360, 385 and 410 mm.

Colour: Transparent. Number per carton: 50.



OPT-BOX68-xxx



Injection moulded pusher tray for 25 pack cigarettes

Pusher with standard spring strengths 2 or 3. Available in lengths: 185, 210, 235, 260, 285, 310, 360, 385 and 410 mm.

Colour: Transparent. Number per carton: 50





OPT-BOX74-xxx



Injection moulded pusher tray for "wider size" pack cigarettes

Pusher with standard spring strengths 2, 3 or 6. Lengths: 310 mm. Transparent. Number per unit: 20.



OPT-BOX86-xxx



Injection moulded pusher tray for "wider size" pack cigarettesPusher with standard spring strengths 2, 3 or 6. Lengths: 310 mm. Transparent.
Number per unit: 20.



OP50-STOP



Pusher stopper for convenient remerchandising


Pusher stopper to be used together with OP50B and OP50B-FL pushers. The stopper grabs and lock the pusher sledge in back position. Height: 73 mm.

Number per carton: 20.

TRAYS AND ACCESSORIES



TRGH



Connectable merchandising "floor"

Sturdy construction allows use in high traffic areas and/or for heavy duty products. The tray is supplied in shock-resistant ABS to withstand wear and tear in high traffic areas. The tray is compatible with all our Optimal™ front rails. The tray is 332.5 mm wide, and comes in two different depths – 385 and 485 mm.





HAM-AVD120



Divider with slide foot for TRGH

Divider lengths 385 and 485 mm. Dividers are inserted from the side, using the front and back channel.



HBS 145 x 101



Back support with slide foot for TRGH

The back support comes in one size approximately 100 mm wide and 145 mm high. Back support resists for up to 10 kg per facing.



осн-



Shelf display for round products

The bevelled divider provides a merchandising solution for round packs where the main display surface is on the top of the pack. A typical example would be a round cheese pack of Camembert.

Available in lengths: 285, 385, 485 and 585 mm. Number per unit: 20.



OPT-TRAYxx-x-0385-0485



Injection moulded pusher tray with rounded front

Pusher with standard spring strengths 3, 6 and 9. Available in widths 47, 50. 52, 55 and 60 mm. One length available 485 mm with break points at 385 and 435 mm.

Colour: Transparent.
Number per unit: 50.



OPT-TRAYxx-0385-0485



Tray for spices

Injection moulded tray for spices. Available with inner width of 43 and 46 mm. $\,$

One length available 485 mm with break points at 385 and 435 mm.

Colour: Transparent. Number per carton: 50.





OPT-TRAY-BF62



Tray for baby food

Injection moulded tray for baby food.

Available in lengths 385, 400, 435, 485, 500 and 535 mm. Colour: Transparent. Number per carton: 32.



OPT-TRAY-BT68-



Tray for beverages

Gravity tray for 0.5 ltr PET bottles and 33 cl cans. Available in lengths 360, 385, 400, 485, 500, 560 and 585 mm. Colour. Transparent. Number per unit: 24.



OPT-TRAY-BT68-6-



Pusher tray for beverages

Pusher tray for 0.5 ltr PET bottles and 33 cl cans. Use spring force 6 for standard applications. Available in lengths 360, 385, 400, 485, 500, 560 and 585 mm. Colour. Transparent. Number per unit: 24.



GBRN



Back support solution

New Back support with 3 strong magnetic tape strips. Can be used with OPRL PIN.





Flat-packed magnetic back support

For simple re-facing of products.

Easily repositioned. Can be supplied pre-printed with eye-catching graphics. Contact us for the possible sizes and modifications. Suitable for fresh food areas where reorganising of products is frequent.

Material: Clear cold resistant 0,7 mm with anti-slip profiled rubber. Packing varies, subject to product dimensions.

⇒ SHELF EDGE SEGMENTATION



EFC20-



Curved branding strip with adhesive tape

Label height 20 mm. A hinge-function allows the label holder to flip-up. Available in transparent.

Number per carton: 75.



OFC20-TP19-




Curved branding strip

Provides an integrated front riser and curved label pocket.
Label height 20 mm. Front riser 14 mm.
Fits most non-wire shelves. Mounted with 19 mm adhesive tape or over an OPB-.

Available in different colours. Number per carton: 75.



OR25-TP19



Brandline - convex label holder.

Supplied with fixing rail and gripper track. Compatible with Optimal accessories and BrandMan shelf tray fronts. Front elevation 17 mm. Mounted with 19 mm adhesive tape. Number per unit 75.



0F25



Brandline convex - front cover

High-gloss, transparent front cover for OR25. Can be cut to size in the store with a pair of scissors. Label height 25 mm. Number per unit 75.



ORC25-TP19



Brandline - concave label holder.

Supplied with fixing rail for dividers and gripper track. Compatible with Optimal accessories and BrandMan shelf tray fronts. Front elevation 17 mm. Mounted with 19 mm adhesive tape. Number per unit 75.





OFC25



Brandline concave - front cover

High-gloss, transparent front cover for ORC25. Can be cut to size in the store with a pair of scissors. Label height 25 mm. Number per unit 75.



BR30-TP19



Brandline flat - label holder.

Supplied gripper track. Segmentation strip which covers a minimum of the pack behind. Front elevation 10 mm.

Mounted with 19 mm adhesive tape. Number per unit 75.



BF30



Brandline convex- front cover

 $\label{thm:bound} \mbox{High-gloss, transparent front cover for BR30-. Can be cut to size in the store}$ with a pair of scissors. Label height 30 mm. Number per unit 75.



OFC30-TP19-



Curved branding strip

Provides an integrated front riser and curved label pocket. Label height 30 mm. Front riser 20 mm. Available in different colours. Fits most non-wire shelves. Mounted with 19 mm adhesive tape. Number per carton: 75.



OFC40-TP19-



Curved branding strip

Provides an integrated front riser and curved label pocket. Label height 40 mm. Front riser 30 mm. Available in different colours. Fits most non-wire shelves. Mounted with 19 mm adhesive tape. Number per carton: 40.






OFRL20-TTP-

Straight branding strip

Provides an integrated front riser and label pocket. Label height 20 mm. Front riser 20 mm. Fits most non-wire shelves. Mounted with 2x9 mm adhesive tape. Available in different colours. Number per carton: 25.





OFC-TRAY-

Injection moulded trayAvailable in widths from 55 to 100 mm, with 5 mm

One length available: 170-370 mm with break points every 50 mm. Total length including OFC30 corresponds to shelf depths from 200 to 400 mm. Colour: Transparent.

Number per unit: 50.



OFC-TRAY-x-

Injection moulded tray with pusher

Pusher with standard spring strengths 3, 6 or 9. Available in widths from 55 to 100 mm, with 5 mm

increments.

One length available: 170-370 mm with break points every 50 mm. Total length including OFC30 corresponds to shelf depths from 200 to 400 mm. Colour: Transparent.

Number per unit: 50.



OPTIFLAG

Flag holder

To be mounted on to the 60 and 120 dividers. To be used with TPL-U-OPT.

Transparent.

Number per unit: 20.



OFC-FLANK



Premium Divider for Product Segmentation

Used with OFC30 or as stand-alone with adhesive. Standard transparent, but can be supplied in colour. Size approximately 180x200 mm.





OPT-HB-HOLDER



Flagholder for OPT-AVD60-HB-

To be mounted on the 60 mm Health and Beauty divider. To be used with the TPL-U-HB. Frosted execution. Number per unit: 20.



OR-FLAG



Flagholder for Brandline railsTransparent flag holder for 1 and 2 mm thick material. Fixes horisontally on the shelf behind Brandline profiles. Grips both into gripper track and Optimal rail for a secure fixation. Number per unit: 20.



OFC-FLAG



Flag holder for curved branding strips

To be mounted on the OFC20 or the OFC30 curved profile. To be used with the TPL-U-HB. Frosted finish. Number per unit: 20



OFC30BR-CLIP60



Brand clip for OFC30

Highlights a specific product or brand. To be mounted over the OFC30 and fixed on the Optimal™ T-rail. For approximately 59x39 mm labels. Frosted finish.

Number per bag: 75.



OFC30BR-CLIP120



Wide Brand Clip for OFC30

Highlights a specific product or brand. Compatible with OFC30. For label size 39x120 mm. Number per unit: 50.






OFC30MULTI-CLIP



Multi clip to OFC30

Allows you to fix customized solutions to the OFC30 rail. To be mounted over the OFC30 and fixed on the Optimal $^{\rm IM}$ T-rail. The customized part can be fixed to the clip with Jegab articles 2302-07, 2302-12, 2302-19 or foam tape. Number per bag: 75.



OFC30-END



Endcap for OFC30

Mounted at the end of the 30 mm branding strip. Colour: Transparent.
Number per bag: 75 pairs.

⇒ BASIC OPTIMAL™ STRIPS



OPB-TP-



Narrow Optimal™ strip

Basic Optimal™ strip. Fits all non-wire shelves. Mounted with 9 mm adhesive tape. Colour: Transparent. Number per carton: 50.



OPH-TP19-



Wide Optimal™ strip

Basic Optimal™ strip with a stronger tape than OPB-TP. Fits all non-wire shelves. Mounted with 19 mm adhesive tape. Colour: Transparent and white. Number per carton: 25.





OPH-TM25-



Wide Optimal™ strip with magnetic tape

Excellent for cool areas. Fits all metal shelves. Mounted with 25 mm magnetic tape. Colour: White. Number per carton: 25.




OBR+TP19



Optimal+™ back strip

Optimal+™ back strip with a 19 mm adhesive tape. Fits all non-wire shelves. Transparent and white. Number per carton: 25.



OBR+ TM25




Optimal+™ back strip with magnetic tape

Optimal+™ back strip with a 25 mm magnetic tape. Fits all metal shelves. Colours: Transparent and white. Number per carton: 25.



OBR+ OW3.0



Optimal+™ back strip for wire shelves

244-495 mm strip includes 2 clips. 496-999 mm strip includes 4 clips. 1000-1377 mm strip includes 6 clips. Fits wire with diameter 2.8 - 3.0 mm. Colour: Transparent. Number per carton: 25.



OPH-OW3.0-



Wide Optimal™ strip for wire shelves

244-495 mm strip includes 2 clips. 496-999 mm strip includes 4 clips. 1000-1377 mm strip includes 6 clips. Fits wire with diameter 2.8 - 3.0 mm. Colour: Transparent.

Number per carton: 25.




OPHW-TTF19-52

Wide Optimal™ strip for gravity feed system

Excellent for gravity feed system when using strongly angled shelves. Fits all non-wire shelves. Mounted with 2x19 mm foam tape. Colour: White.

Number per carton: 25.





Optimal[™] strip for Tegometall shelves Fits U-channels at front and rear.

Colour: Transparent.
Number per carton: 50.





Optimal strip for Wanzel Wire Tech

Fits Wanzel wire Tech shelves DBR front, available in different colours, is assembled on the rear piece. Label height 26, 30, 35, 39, 45, 52, 76 or 76mm. Number per carton: 100.

○ OPTIMAL™ STRIPS FOR ASSEMBLY WITH DATASTRIP



OGLS10-



Optimal™ strip for glass, wood and metal shelves

For shelves 7-10 mm thick.

DBR front, available in different colours, is assembled on the rear piece.

Label height 26, 30, 35, 39, 45, 52, 70 or 76 mm. Number per carton: 25.



OANTL-



Optimal™ strip for 19-25 mm shelves

The OANTL can be used at the front and rear of the shelf to fix the dividers without any tape.

DBR front, available in different colours, is assembled on the rear piece.

Label height 26, 30, 35, 39, 45, 52, 70 or 76 mm. Number per carton: 50.





OPT-TP19



Optimal™ strip that can hold a front riser

Possibility to mount an OPT-FR front riser on the strip. DBR front, available in different colours, is assembled on the rear piece.

on the rear piece.
Label height 26, 30, 35, 39, 45, 52, 70 or 76 mm.
19 mm adhesive tape. Fits most non-wire shelves.
26-39 mm, number per carton: 20.
45-76 mm, number per carton: 15.





OTR





Optimal™ strip for wire shelves

Allows an OPT-FR front riser to be mounted on the strip. Fits wire shelves with inner front height of 12-17 mm. DBR front, available in different colours, is assembled on the rear piece.

26-39 mm, number per carton: 25. 45-76 mm, number per carton: 15.



 \oplus



⇒ FRONT RISERS OPTIMAL™



OFRK30-TTP-, OFRK40-TTP-



Low front risers

Provides an integrated front riser to prevent merchandise from falling over the shelf edge.

Fits all non-wire shelves. Mounted with 2x9 mm adhesive tape.

Colour: Transparent or transparent with white base.

OFRK30, number per carton: 25.

OFRK40, number per carton: 30.



OFRK30-OW3.0-, OFRK40-OW3.0-



Low front risers for wire shelves

244-495 mm strip includes 2 clips.
496-999 mm strip includes 4 clips.
1000-1377 mm strip includes 6 clips.
Fits wire with diameter 2.8 - 3.0 mm.
Colour: Transparent or transparent with white base.
OFRK30, number per carton: 25.
OFRK40, number per carton: 30.



OFRK30-TM25-, OFRK40-TM25-



Low front riser with magnetic tape

Excellent for cool areas (coolers 6-10 $^{\circ}$ C) when a front riser is needed.

Fits all metal shelves.

Mounted with 25 mm magnetic tape.

Colour: Transparent or transparent with white base.

OFRK30, number per carton: 25. OFRK40, number per carton: 30.



OFRK60-TTP19-, OFRK80-TTP19-




High front riser

Provides an integrated front riser to prevent merchandise from falling over the shelf edge. Fits all non-wire shelves.

Mounted with 2x19 mm adhesive tape.
Colour: Transparent or transparent with white base.
OFRK60, number per carton: 25.
OFRK80, number per carton: 25.






OFRK60-0W3,0-, OFRK80-0W3,0-






High front riser for wire shelves

244-495 mm strip includes 2 clips.
496-999 mm strip includes 4 clips.
1000-1377 mm strip includes 6 clips.
Fits wire diameter 2.8-3.0 mm.
Colour: Transparent or transparent with coloured base.
OFRK60, number per carton: 25.







OFRK60-TTM25-, OFRK80-TTM25-



High front riser with magnetic tape

Excellent for cool areas (coolers 6-10°C) when a front riser is needed.

Fits all metal shelves. Mounted with 2x25 mm magnetic tape.

Colour: Transparent or transparent with white base. OFRK60, number per carton: 25.

OFRK80, number per carton: 25.





OFRKB3-TTP19-



Base for front riser

A two part solution for a front riser.

Allows an OPT-FR front riser of thickness 3.0 mm to be mounted on the base rail.

Fits all non-wire shelves.

Mounted with 2x19 mm adhesive tape.

Colour: Transparent or white.

Number per carton: 25.





OPT-FR-



Front riser

Front riser that can be used with OPT-TP19, OTR or OTEF.

Standard height: 63 or 79 mm.

Length: Any length.

Screen print available.

Packing varies, subject to product dimensions.





OFRK80A30-TTF19-



Angled front riser for gravity feed

30° angled front riser to be used with our gravity

Fits all non-wire shelves. Mounted with 2x19 mm foam tape.

Colour: Transparent or transparent with white base.

Number per carton: 20.

DIVIDERS WITH T- OR L-FOOT




AT80C-length-RH, AT80C-

Dividers for freezers and coolers

80 mm high divider without grip. Available with (AT80C-length-RH) or without (AT80C-) rounded corners. Colour: Transparent.
Number per carton: 10.






Extra clear divider for freezers and coolers

80 mm high divider without grip Available with (AT80E-length-RH) and without (AT80E-) rounded corners. Colour: Transparent. Number per carton: 10.






Divider for freezers and coolers

150 mm high divider without grip. Available in lengths 280, 380, 480, 580, 680 and 780 mm. Number per unit: 10.




 \oplus



L-shaped divider for freezers and coolers

Customised sizes and shapes possible. Thickness: 2, 3 or 4 mm. Can be screen-printed. Packing varies, subject to product dimensions.





T-shaped divider with hinged feet

For freezer and refrigerated areas. Feet with hinge function. Guaranteed 90° angle. Rounded corners, flat pack delivered. Graphics: Screen printed. Packing varies, subject to product dimensions.

PULL-OUT SHELVES





Space saving pull-out shelf - 10 kg load

Optishelf™ 10 is an extendable shelf with a maximum load of 10 kg. The locking device operates in stored and in extended position. The shelf is designed to be used in conjunction with Optimal™ dividers and pushers or cigarette cassettes. The shelf exists in widths from 600 to 1000 mm c/c and in depth of 300, 400 and 415 mm. For only horizontal setting. Standard colours: White (RAL 9010), black (RAL 9005), IKEA silver (4), grey (0022).

Article code: OPS-10 d-w co

d: depth w: width

co: colour code.



(

 \oplus

 \oplus





OPS-18

Space saving pull-out shelf - 18 kg load

Optishelf™ 18 is an extendable shelf with a maximum load of 18 kg. The locking device operates in stored and in extended position.

Widths: From 600 to 1240 mm c/c. Depth: 400 mm. The shelf can be set straight or at a 15 degree angle.

Standard colours: White (RAL 9010), black (RAL 9005), IKEA silver (4), grey (0022).

Article code: OPS-18 d-w a co

d: depth w: width

a: angle

co: colour code





OPS-50

Space saving pull-out shelf - 50 kg load

Is a pull-out shelf that can be extended to 75% of its depth.

Maximum load on the shelf in its extended position is 50 kg. The shelf can be ordered with a width from 600 to 1330 c/c mm and with a depth of either 400 or 500 mm. The shelf is fitted with tension spring to facilitate returning the shelf to its back position. Horizontal and 15 degree angle position setting is standard. Adapted brackets and locking devices on request. Standard colours: White (RAL 9010), black (RAL 9005), IKEA silver (4), grey (0022).

Article code: OPS-50 d-w a co

d: depth

w: width

a: angle

co: colour code.





OPS-100

Space saving pull-out shelf - 100 kg load

OPS100 is a special designed heavy duty pull-out shelf, especially developed for product categories there wide shelving are used and categories where product weight exceeds 50 kg per shelf. The shelf permits loading weights up to 100 kg. The shelf exists in widths from 900 to 1330 c/c mm, depth 500 mm only. For only horizontal setting.

Standard colours: White (RAL 9010), black (RAL 9005), IKEA silver (4), grey (0022).

Article code: OPS-100 d-w a p co

d: depth w: width

a: angle p: pitch

co: colour code.









